

REMARKS/ARGUMENTS

Claims 1-14 and 17 are pending in the present application. By this reply, claims 15 and 16 have been canceled and claims 17 has been added. Claims 1 and 14 are independent claims.

Title of the Invention

At the Examiner's request, a new title is provided.

Drawing Objection

The drawings have been objected to because they allegedly fail to show the features of the invention specified in the claims. To overcome this drawing objection, claims 15 and 16 have been canceled and claim 14 has been modified. The features recited in modified claim 14 are shown in Figs. 1-3D. Accordingly, reconsideration and withdrawal of the drawing objection are respectfully requested.

35 U.S.C. § 112, Second Paragraph, Rejection

Claims 14-16 have been rejected under 35 U.S.C. § 112, second paragraph, as being indefinite. To overcome this rejection, claims 15 and 16 have been canceled and claim 14 has been modified to be in full compliance

with 35 U.S.C. § 112, second paragraph. Accordingly, the rejection should be withdrawn.

35 U.S.C. § 103 Rejection

Claims 1-13 have been rejected under 35 U.S.C. § 103(a) as being unpatentable over Applicant's disclosed background art. This rejection, insofar as it pertains to the presently pending claims, is respectfully traversed.

Applicant's disclosed background art suggests an apparatus for displaying many complicated audio settings menus including *unusable* audio settings menus on a screen of the display apparatus. But, when many complicated audio settings menus, including unusable audio settings menus, are displayed on the screen of the display apparatus, they cause confusion and inconvenience to the user, and the user can not listen to the audio properly when the unusable audio settings menu is selected.

In contrast, Applicant's embodied invention is capable of preventing the user from setting audio options incorrectly and allowing the user to select from the usable audio settings menus conveniently by displaying only the usable audio settings menus on the display apparatus. The usable audio settings menus are determined based on the connection state of audio output terminals and audio source information. This feature is neither taught nor suggested by Applicant's background art.

Accordingly, the invention as recited in independent claim 1 and its dependent claims (due to their dependency) is patentable over Applicant's disclosed background art, and the rejection should be withdrawn.

Claim 15 has been rejected under 35 U.S.C. § 103(a) as being unpatentable over Jordan et al. Claim 16 has been rejected under 35 U.S.C. § 103(a) as being unpatentable over Jordan et al. in view of Waldron or Brown.

In view of the cancellation of claims 15 and 16, the rejections are moot and should be withdrawn.

35 U.S.C. § 102(e) Rejection

Claim 14 has been rejected under 35 U.S.C. § 102(e) as being anticipated by Jordan et al. This rejection, insofar as it pertains to the presently pending claims, is respectfully traversed.

Jordan et al. is directed to displaying video on a monitor of a digital television system, wherein the external audio may be connected by way of external speakers or amplifiers. The system of Jordan et al. teaches that other information may be included in the preference menu, such as the audio connection, external video names, etc. However, the system of Jordan et al. does not teach or suggest the means for determining usable audio settings menus based on the connection state and audio source information, wherein only the determined usable audio settings menus are displayed on the display, as required by claim 14. Thus, the system of Jordan is not capable of

preventing the user from setting audio menus incorrectly and of exactly and conveniently selecting the usable audio settings menu by displaying only the usable audio settings menus on the display, as in Applicant's embodied invention.

Accordingly, the rejection of claim 14 should be withdrawn.

CONCLUSION

For the foregoing reasons and in view of the above clarifying amendments, Applicant respectfully requests the Examiner to reconsider and withdraw all of the objections and rejections of record, and earnestly solicits an early issuance of a Notice of Allowance.

Should there be any outstanding matters which need to be resolved in the present application, the Examiner is respectfully requested to contact Esther H. Chong (Registration No. 40,953) at the telephone number of the undersigned below, to conduct an interview in an effort to expedite prosecution in connection with the present application.

If necessary, the Commissioner is hereby authorized in this, concurrent, and further replies, to charge payment or credit any overpayment to Deposit Account No. 02-2448 for any additional fees required under 37 C.F.R. § 1.16 or under 37 C.F.R. § 1.17; particularly, extension of time fees.

Respectfully submitted,

BIRCH, STEWART, KOLASH & BIRCH, LLP

By *Joseph A. Kolasch* #40,953
Joseph A. Kolasch, #22,463

P.O. Box 747
Falls Church, VA 22032-0747
(703) 205-8000

JAK/EHC:lmh

Enclosures: Substitute Specification
Marked-Up Copy of Specification
Abstract of the Disclosure

METHOD FOR DISPLAYING AUDIO SETTINGS
MENU OF DISPLAY METHOD APPARATUS

BACKGROUND OF THE INVENTION

1. Field of the Invention

[001] The present invention relates to an audio menu display method, in particular to a method for displaying and selecting a multi-channel audio menu and an apparatus thereof.

2. Description of the Prior Art

[002] Among various display apparatus, there is an ATSC (advanced Television System Committee), a NTSC (National Television Standard Committee), a satellite broadcast, a SPDIF (Sony Philips Digital Interface), and an analog left/right input as an audio source inputtable to a digital television (DTV). There is a speaker output and a monitor output as an analog output from the DTV to ~~outside~~
an external device.

[003] Herein, the speaker output is connected to an outer speaker in order to output a signal amplified in the DTV, and the monitor output is connected to a power amplifier installed outside of the DTV for better sound quality.

[004] In general, a television has a speaker output, and a DVD (digital Versatile Disc) or a set-top box has only a monitor output.

[005] FIG. 1 is a block diagram illustrating audio sources inputtable to a DTV, a speaker output, and a monitor output.

[006] A DTV 5 receives signals from the inputtable sources such as a satellite broadcast source 1, a terrestrial broadcast source 2, a SPDIF (Sony Philips

Digital Interface) digital signal source 3, an analog left/right source 4, and outputs an audio signal by processing the input signals through a built-in speaker 5-1, a speaker output terminal 5-2, and a monitor output terminal 5-3. Herein, the speaker output terminal 5-2 outputs an audio signal through a speaker 6, and the monitor output terminal outputs an audio signal. An outer external amplifier 7 amplifies the monitor output and transfers it to the speaker 6.

[007] Below Table 1 describes the inputtable sources and the number of channels of the each source.

[Table 1]

Source	Kind of audio	The number of channel
Terrestrial ATSC	AC-3	1 ~ 5.1
Terrestrial NTSC	Analog L/R	2
Satellite broadcast	AC-3	2 ~ 5.1
	MPEG	2
SPDIF digital input	AC-3	1 ~ 5.1
	MPEG	2
	PCM	2
Analog L/R input	Analog L/R	2

[008] Herein, a user can listen to audio through an internal speaker of the DTV, however, the performance of the internal speaker of the DTV is not as good as the performance of the outer (external) speaker. Although, three internal speakers can generally be installed on the left, right, and center of the DTV, a user who wants to listen to better sound or a viewer who wants to enjoy a surround or a subwoofer has to connect the outer speaker to the speaker output terminal of the DTV or has to

connect the outer power amplifier to the monitor output terminal of the television.

[009] Meanwhile, ~~When~~ when 5.1 channels are embodied on the DTV, because the sources of the DTV and channels of the sources are various, there can be lots of user selectable menus, ~~the~~. The audio menu displayed on the analog television is no match for that. For example, when the 5.1 channels are embodied, user selectable menus can be described as below.

Example 1. Listening Mode

[010] The selectable menus in accordance with the number of the outer speakers connected to the speaker output terminals of the DTV and the number of the terminals of the outer amplifiers connected to the monitor outputs can be described as below in Table 2.

[Table 2]

Listening Mode	
Dolby digital	Left/center/left surround/right surround/subwoofer
Dolby prologic	Left/right/center/mono surround
Phantom center	Left/right/left surround/right/surround/subwoofer
3 stereo	Left/right/center
Stereo	Left/right
Mono	

Example 2. Balance Control

[011] In order to balance outputs of left/right and left surround/right surround audio signals, a balance control is performed as below.

[Table 3]

Balance Control
Left-Right Balance
Left Surround-Right Surround Balance

Example 3. Channel Delay

[012] For optimum listening circumstances, as depicted in FIG.4 Table 4, an output delay of an audio channel is adjusted so as to transmit the sound of front channels (L/R/C) and the sound of back channels (Left surround/ Right surround) to the viewer at the same time.

[Table 4]

Channel Delay
Surround time Delay
Center time Delay

~~Example 4~~ Example 4. Volume Control

[013] It can be described as below.

[Table 5]

Volume Control	
Master Volume Control	Volume Control about all channels
Volume Control about each channel	
Test Mode	Listen a set volume of the each channel

Example 5. Output Construction

[014] A construction 1 and 2 described in Table 6 are for Dolby certification. According to "Licensing Information Manual" of Dolby Lab., 5.1ch DTV should have this configuration. Herein, a name of the menu can be determined appropriately.

[Table 6]

Output Configuration	
Construction 1	Separate low-pass elements from the L/R/C/Ls/Rs channels and transmit them to the subwoofer
Construction 2	Separate low-pass elements from the C/Ls/Rs channels and transmit them to the subwoofer
Construction 3	Option item

Example 6. Additional audio service functions

[015] A digital audio signal is decoded in accordance with regulated compression standards such as an AC (audio Coding) –3 or a MPEG (Moving Picture Expert Group) etc., and is transmitted. It is possible to perform below audio services in the AC –3/MPEG.

- VI: Visually Impaired
- HI: Hearing Impaired
- ME: Music and Effects, used with Dialogue
- Dialogue: used with ME, and used for a multilingual service
- C: Commentary, comments about a program
- E: Emergency, inform an emergency
- VO: Voice Over, Overlap audio with existing broadcast audio

Example 7. Additional Menus

- Multilingual audio selection menu
- similar stereo: Make stereo with Mono source
- Front Surround: Make surround effect with a left and a right speakers
- Dynamic Range Compression On/Off: Reproduce dynamic range of AC-3 or reproduce the dynamic range of AC-3 as it is
- Prologic On/Off: When an AC-3/MPEG source encoded with Dolby prologic or 2 channel analog signal and a digital PCM signal are inputted from outside, determine automatically whether a prologic processing is performed or not

[016] As described in Examples 1 ~ 7, lots of audio menus can exist when the DTV is embodied with 5.1 channels in accordance with the conventional technology. However, the number of actual usable menus are strictly limited in accordance with the number of outer speakers connected to the speaker output terminals of the DTV or the number of outer amplifier terminals connected to the monitor output terminals, the present audio input selected among a plurality of audio inputs, and in case of the AC-3, the number of channels and the kind of services.

[017] Accordingly, ~~the lots of~~ these audio menus can cause confusion and inconvenience ~~of~~ to the user, and the user can not listen to the audio properly when the wrong menu is selected.

SUMMARY OF THE INVENTION

~~The~~**[018]** An object of the present invention is to provide an audio menu

display method and an apparatus thereof which ~~is~~ are capable of displaying only usable audio menus by being connected to a DTV.

[019] In order to achieve the above-mentioned ~~object~~ and other objects, the audio menu display method of the DTV in accordance with the present invention comprises detecting a connection state of audio output terminals, getting audio source information from audio source content received from the DTV, determining a usable audio menu for displaying on a certain screen in accordance with the connection state and audio source information, and displaying the determined usable audio menu on the screen.

[020] The audio menu display apparatus of a digital television in accordance with the present invention comprises a display for displaying video, and a CPU for displaying an audio menu on the display.

[021] These and other objects of the present application will become more readily apparent from the detailed description given hereinafter. However, it should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

BRIEF DESCRIPTION OF THE DRAWINGS

[022] The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus are not limitative of the present invention and wherein:

[023] FIG.1 is a block diagram illustrating audio sources inputtable to a DTV, a speaker output, and a monitor output.

[024] FIG.2A is a block diagram illustrating speaker output terminals in accordance with the present invention.

[025] FIG.2B is a block diagram illustrating monitor output terminals in accordance with the present invention.

[026] FIG.3A ~ 3D illustrate examples of the monitor output terminal in accordance with the present invention.

[027] FIG.4 is a flow chart illustrating an audio menu display method in accordance with the present invention.

[028] FIG.5 is a flow chart illustrating a method for getting information of an audio source in accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

EMBODIMENTS

[029] The present invention relates to an audio display method and an apparatus thereof which ~~is~~ are capable of displaying only user usable audio menus among a plurality of audio menus, ~~the~~ The user usable menus can be determined by considering the number of outer speakers connected to speaker output terminals of a TV or the number of outer amplifier channels (or terminals) connected to monitor output terminals, and the present selection of audio input among a plurality of audio inputs. For example, the usable audio menus are determined by considering the number of channels, and the kind of services in an AC-3/MPEG.

[030] First, a method for determining the actual usable audio menu will now be described.

[031] The number of the outer speakers connected to the speaker output terminals of the DTV or the number of the outer amplifier terminals connected to the

monitor output terminals are determined. Herein, terminals capable of knowing a connection state of the terminals are used for the speaker output terminals and monitor output terminals. For example, when the terminal is in the connection state, high voltage is outputted,~~when.~~ When the terminal is not in the connection state, a low voltage is outputted. Accordingly, when the output voltages are inputted to a CPU (not shown) in a DTV, the CPU can know the present connection state of the speaker output terminal or monitor output terminal.

[032] FIG.2A is a block diagram illustrating speaker output terminals in accordance with the present invention, the output terminals having a clip form which can be used. Herein, L1 and L2 are holes for connecting each signal line.

[033] FIG.2B is a block diagram illustrating monitor output terminals in accordance with the present invention. As shown, RCA terminals can be used.

[034] FIG.3A is a front view of a male connector of a speaker output terminal in accordance with the present invention, and FIG.3B is a side view of the side connector of the speaker output terminal.

[035] FIG.3C is a side view illustrating a female connector of the speaker output terminal in accordance with the present invention, and FIG.3D is a side view illustrating a connection state of the male connector and female connector,~~it.~~ It is designed to ~~know-possible~~ recognize the ON/OFF state of the speaker output terminal automatically and mechanically.

[036] FIG.4 is a flow chart illustrating an audio menu display method in accordance with the present invention,~~an.~~ An audio menu is displayed by detecting the connection state of the present speaker output terminal or monitor output terminal by a CPU.

[037] First, the CPU (e.g., in the DTV) detects the connection state of the speaker output terminal or monitor output terminal of the DTV. For example, the

number of the speakers connected to the DTV or the number of the outer amplifier terminals connected to the monitor output terminals is detected S10. Then, audio source information selected by the user and audio source content information received to the DTV is ~~gotten~~ obtained S20.

[038] When the user changes the audio input source, for example, the user changes a channel, the detecting process of step S20 is performed, as described above, because the audio source, namely, the program is changed. The detecting process of step S20 is performed whenever the audio source is changed.

[039] Herein, the content of the audio source can be detected by referencing program information or content of an audio stream in case of the ATSC or satellite broadcast. In addition, in case of digital audio input as the SPDIF (Sony Philips Digital Interface), the content of the audio source can be detected by referencing the content of the audio stream.

[040] Accordingly, the ~~proposed~~ present method detects the number of the speakers connected to the TV speaker output terminals or number of the outer amplifier terminals connected to the monitor output terminals, and the present selection of audio input and content of the audio source, ~~and~~ determines the present usable audio menus S30, and displays only the determined usable menus on the screen S40 when the user selects an audio menu.

[041] FIG.5 is a flow chart illustrating a method for getting information of an audio source in accordance with the present invention.

[042] For example, when the selected audio source is encoded with the AC-3 S21, the CPU can get the audio source information for example by checking the number of channels, whether or not the prologic encoding, in present, the existence of the subwoofer channel, the existence of the multilingual service, existence of the additional audio service, etc. at S22, ~~on.~~ On the contrary, when the selected audio

source is not encoded with the AC-3, the CPU can get the audio source information by checking whether or not ~~stereo/mono~~ S23.

the system is in stereo/mono state S23.

[043] The methods of FIGS. 4 and 5 can be implemented using existing hardware such as one shown in FIG. 1, if it is electronically configured to implement the present methods.

[044] The displayed audio menu will now be described in more detail in accordance with the audio source information.

[045] For example, if the audio source is a terrestrial ATSC, the kind of the audio is the AC-3 encoding, and the number of the channels is 5.1. In addition, three outer speakers are connected to a left L, a right R, and a center C of the actual speaker output terminals, and two outer amplifier terminals are connected to a left L and a right R of the monitor output terminals.

Example 1. Listening Mode

[046] Because the number of the outer speakers connected to the speaker output terminals of the DTV is three (L, R, C) and the number of the outer amplifiers connected to the monitor outputs is two (L, R), as depicted in ~~FIG. 7~~ Table 7, the user selectable menu can be described as below Table 7.

[Table 7]

Listening Mode	
3 Stereo	Left/Right/Center
Stereo	Left/Right
Mono	

[047] Example 2. Balance Control

[048] Because the surround is not connected, the balance control can be described as below Table 8.

[Table 8]

Balance Control
Left-Right Balance

Example 3. Channel Delay

[049] In order to ~~make~~ allow the viewer to listen to the sound in the optimum listening circumstances, ~~as depicted in FIG.4,~~ the output delay of an audio signal is adjusted so as to transmit the sound of the front channels L/R/C and the sound of the back channels (Left Surround/Right Surround) to the viewer at the same time. Herein, the Surround is not connected, and accordingly it is not displayed.

Example 4. Volume Control

[050] It is displayed about the L, R, C channels, ~~it~~ which can be described as below Table 9.

[Table 9]

Volume Control	
Master Volume Control	Volume Control about the L, R, C channels
Volume Control about the L, R, C channels	
Test Mode	Listen a set volume of the each L, R, C channel

Example 5. Output construction

[051] Because there is no subwoofer, it is not displayed.

Example 6. Additional audio service functions

[052] Below additional audio services are possible in the AC-3/MPEG.

- VI: Visually Impaired
- HI: Hearing Impaired
- ME: Music and Effects, used with Dialogue
- Dialogue: used with ME, and used for a multilingual service
- C : Commentary, comments about a program
- E: Emergency, inform an emergency
- VO: Voice Over, Overlap audio with existing broadcast audio

Example 7. Additional menus

- Multilingual select menu
- similar stereo : Make stereo with Mono source
- Front Surround : Make surround effect with a left and a right speakers
- Dynamic Range Compression On/Off : Reproduce dynamic range of AC-3 after reducing it or reproduce the dynamic range of AC-3 as it is

[053] Accordingly, the displayed audio menus are strictly limited in accordance with the number of outer speakers connected to the speaker output terminal of the TV or the number of the outer amplifier terminals connected to the

monitor output terminal, the present audio input selected among a plurality of audio inputs, and in the AC-3, the number of channels and kind of services.

[054] The present invention can be adapted to audio menus of a set-top box, an A/V amplifier, an A/V receiver as well as the DTV.

[055] The above-described audio menu display method and an apparatus thereof in accordance with present invention is are capable of preventing the user from setting audio menus wrongfully, and selecting the audio menu conveniently by displaying only the present usable audio menus to the user. Particularly, when the 5.1 channels are embodied, because the present invention arranges many and complicated audio menus and displays only the present usable menus to the user, it is possible to provide convenience to the user in the audio menu select.